

Chapter 5

Compacting and Finishing

Part 2

Compaction Operations

- After selecting appropriate compaction equipment, a **compaction plan** must be developed.
- The major variables to be considered include:
 1. soil moisture content,
 2. lift thickness,
 3. number of passes used,
 4. ground contact pressure,
 5. compactor weight, and
 6. compactor speed.
- For vibratory compactors, it is also necessary to consider
 7. the frequency and amplitude of vibration to be employed.


Compaction Operations

- 1. soil moisture content
 - the compactive effort delivered by a piece of compaction equipment will seldom be exactly the same as that of either the standard or modified compaction test.
 - Thus, the field optimum moisture content for a particular soil/compactor combination will seldom be the same as the laboratory optimum.

Compaction Operations

- This is illustrated by Figure 5-11, where only one of the four compactors has a field optimum moisture content close to the laboratory optimum.

FIGURE 5-11: Variation of optimum moisture content with roller type.
(From reference 6)



THE EFFECT OF MOISTURE CONTENT ON THE DRY DENSITY OF A SILTY CLAY (CL) SOIL IN 9in. LOOSE LAYERS WHEN FULLY COMPACTED BY UP TO 64 PASSES BY DIFFERENT TYPES OF COMPACTING EQUIPMENT.


Compaction Operations

- 2. Lifts thicknesses :
 - It should be kept thin for most effective compaction.
 - For all rollers, except vibratory rollers and heavy pneumatic rollers, a maximum of 5 to 8 in. (15 to 20 cm).
 - The maximum lift thickness depends on the static weight of the compactor.

Compaction Operations

- 3. number of passes
- The compaction achieved by repeated passes:
 - The compaction achieved by repeated passes of a compactor depends on the soil/compactor combination utilized.
 - For some combinations (such as a tamping foot roller compacting a clayey gravel), significant increases in density may continue to occur beyond 50 passes.
 - As shown in Figure 5-12, the increase in density is relatively small after about 10 passes for most soil/compactor combinations.

FIGURE 5-12: Typical effect of number of passes.



- 4. Effect of Ground contact pressure on Compaction:
 - for a tamping foot roller, Ground contact pressure may vary from:
 - 30 lb/sq in. (207 kPa) for a pneumatic roller to
 - 300 lb/sq in. (2070 kPa) or more for tamping foot rollers.
 - Within these ranges it has been found that:
 - total roller weight has a much more pronounced effect on the compaction achieved than does contact pressure.
 - The use of excessive ground contact pressure will result in **shearing and displacement** of the soil being compacted.

- **6. Effect of Travel time on Compaction:**
 - Except for vibratory compactors, tests have shown little relationship between compactor travel speed and the compaction achieved.
 - For vibratory equipment,
 - travel speed (at a fixed operating frequency) determines the number of vibrations that each point on the ground surface will receive.
 - Therefore, when using vibratory equipment, tests should be performed to determine the compactor speed that results in the highest compactor productivity.
 - For **conventional equipment** the highest possible speed should be utilized that does not result in excessive surface displacement.

Estimating Compactor Production

- Equation 5-1 may be used to calculate compactor production based on:
 - compactor speed,
 - lift thickness, and
 - effective width of compaction.
- The accuracy of the result obtained will depend on the accuracy in estimating speed and lift thickness.
- Trial operations will usually be necessary to obtain accurate estimates of these factors.
- Typical compactor operating speeds are given in Table 5-3.

TABLE 5-3: Typical operating speed of compaction equipment

Compactor	Speed	
	<i>mi/h</i>	<i>km/h</i>
Tamping foot, crawler-towed	3–5	5–8
Tamping foot, wheel-tractor-towed	5–10	8–16
High-speed tamping foot		
First two or three passes	3–5	5–8
Walking out	8–12	13–19
Final passes	10–14	16–23
Heavy pneumatic	3–5	5–8
Multitired pneumatic	5–15	8–24
Grid roller		
Crawler-towed	3–5	5–8
Wheel-tractor-towed	10–12	16–19
Segmented pad	5–15	8–24
Smooth wheel	2–4	3–6
Vibratory		
Plate	0.6–1.2	1–2
Roller	1–2	2–3

Estimating Compactor Production

$$\text{Production (CCY/h)} = 16.3 \times W \times S \times L \times E / P \quad (5-1A)$$

$$\text{Production (CCM/h)} = 10 \times W \times S \times L \times E / P \quad (5-1B)$$

Where

P = number of passes required

W = width compacted per pass (ft or m)

S = compactor speed (mi/h or km/h)

L = compacted lift thickness (in. or cm)

E = job efficiency

Estimating Compactor Production

- The power required to tow rollers depends on the roller's total resistance (grade plus rolling resistance).
 - The rolling resistance of tamping foot rollers has been found to be approximately 450 to 500 lb/ton (225 to 250 kg/t).
 - The rolling resistance of pneumatic rollers and the maximum vehicle speed may be calculated by the methods of Chapter 4.

Job Management

- trial operations are usually required to determine:
 - the exact values of soil moisture content,
 - lift thickness,
 - compactor weight, and
 - vibrator frequency and amplitude that yield maximum productivity while achieving the specified soil density.
- The use of a nuclear density device to measure the soil density actually being obtained during compaction is strongly recommended.

Job Management

- Traffic planning and control is an important factor in compaction operations.
- Hauling equipment must be given the right-of-way without excessively interfering with compaction operations.

5-3 SOIL STABILIZATION

- *Soil stabilization* has been defined as:
 - the process of giving natural soils enough abrasive resistance and shear strength to accommodate traffic or loads.
- Soil stabilization methods include:
 - mechanical methods,
 - hydraulic methods,
 - reinforcement methods ,and
 - physiochemical methods.
- Some techniques falling under each of these categories are shown in Table 5-4.

TABLE 5-4: Soil stabilization methods

Mechanical	Hydraulic	Reinforcement	Physiochemical
Compaction	Drainage	Confinement	Admixtures
Deep compaction	Preloading	Inclusions	Freezing
Vibroflotation	Electroosmosis	Minipiles	Grouting
		Soil nailing	Heating
		Stone columns	

- Deep compaction: dropping heavy weight (9-36 t) from a crane (15-30m) to increase the density of soil to a depth of up to 9 m.
- Vibroflotation: increasing density of cohesionless soil by inserting a vibratory probe into soil.
- Electroosmosis: employs electrical current to speed up the drainage of cohesive soils.

5-4 GRADING AND FINISHING

- *Grading* is the process of bringing earthwork to the desired shape and elevation (or grade).
- *Finish grading*, or simply *finishing*, involves:
 - smoothing slopes,
 - shaping ditches, and
 - bringing the earthwork to the elevation required by the plans and specification.
- Finishing usually follows closely behind excavation, compaction, and grading.
- Finishing, in turn, is usually followed closely by seeding or sodding (grass) to control soil erosion.

5-4 GRADING AND FINISHING

- The piece of equipment most widely used for grading and finishing is the motor grader (Figure 5-13).
- Grade trimmers and excavators are frequently used on large highway and airfield projects
 - because their operating speed is greater than that of the motor grader.

FIGURE 5-13: Modern motor grader.

(Courtesy of Fiatallis North America, Inc.)

<https://www.youtube.com/watch?v=bFoN5LD0Q-w>

https://www.youtube.com/watch?v=ZNWafIsql_g



- In highway construction,
 - the process of cutting down high spots and filling in low spots of each roadway layer is called *balancing*.
 - *Trimming* is the process of bringing each roadway layer to its final grade.

- **Motor Grader**
- **Grade Excavators and Trimmers**
- **Estimating Grader Production**
- **Job Management**

Motor Grader

- The *motor grader* is one of the most versatile items of earthmoving equipment.
- It can be used for:
 - light stripping,
 - grading,
 - finishing,
 - trimming,
 - bank sloping,
 - ditching,
 - backfilling, and
 - scarifying.

Motor Grader

- It is also :
 - capable of mixing and spreading soil and asphaltic mixtures.
 - used on building construction projects as well as in heavy and highway construction.
 - It is frequently used for the maintenance of highways and haul roads.


Motor Grader

- The blade of a motor grader:
 - is referred to as a *moldboard* and is equipped with replaceable cutting edges and end pieces (end bits).
 - The wide range of possible blade positions is illustrated in Figure 5-15.

FIGURE 5-15: Blade positions for the motor grader.

(U.S. Department of the Army)

<https://www.youtube.com/watch?v=S1GSljGjsg>




Motor Grader


- Motor graders are available with articulated frames that increase grader maneuverability.
- The three possible modes of operation for an articulated grader are illustrated in Figure 5-16.

FIGURE 5-16: Articulated grader positions.

<https://www.youtube.com/watch?v=JQXaW2svM7w>



- The machine operation modes are:
 - **Conventional manner** when in the straight mode (Figure 5-16A).
 - **Articulated mode** (Figure 5-16B) to allow the machine to turn in a short radius.
 - **The crab mode** (Figure 5-16C) permits the rear driving wheels to be offset so that they remain on firm ground while the machine cuts banks, side slopes, or ditches.



Motor Grader

- The front wheels of both conventional and articulated graders may be **leaned from side to side**.
- Wheels are leaned away from the cut to:
 - offset the side thrust produced by soil pressure against the angled blade.
 - assist in turning the grader.



Motor Grader

- Graders are available with automatic blade control systems that:
 - permit precise grade control.
 - utilize a sensing system that follows an existing surface, string line, or laser beam to automatically raise or lower the blade as required to achieve the desired grade.

Grade Excavators and Trimmers

- *Grade excavators or trimmers:*
 - they are machines that are capable of finishing roadway and airfield subgrades and bases faster and more accurately than can motor graders.
 - Many of these machines also act as reclaimers.
 - they are capable of scarifying and removing soil and old asphalt pavement.

FIGURE 5-17: Large grade trimmer/reclaimer/paver.
(Courtesy of CMI Corp.)



Grade Excavators and Trimmers

- Grade trimmers:
 - They lack the versatility of motor graders.
 - They are very useful on large roadway and airfield projects.
 - Because of their accuracy and high speed.
 - Their large size often requires that they be partially disassembled and transported between job sites on heavy equipment trailers.

Estimating Grader Production

- Grader production is usually calculated:
 - on a linear basis (miles or kilometers completed per hour) for roadway projects and
 - on an area basis (square yards or square meters per hour) for general construction projects.
- The time required to complete a roadway project may be estimated as follows:

$$\text{Time (h)} = \left[\sum \frac{\text{Number of passes} \times \text{Section length (mi or km)}}{\text{Average speed for section (mi/h or km/h)}} \right] \times \frac{1}{\text{Efficiency}} \quad (5-2)$$

Estimating Grader Production

- Average speed will depend on:
 - operator skill,
 - machine characteristics, and
 - job conditions.
- Typical grader speeds for various types of operations are given in Table 5-6.

TABLE 5-6: Typical grader operating speed

Operation	Speed	
	<i>mi/h</i>	<i>km/h</i>
Bank sloping	2.5	4.0
Ditching	2.5–4.0	4.0–6.4
Finishing	4.0–9.0	6.5–14.5
Grading and road maintenance	4.2–6.0	6.4–9.7
Mixing	9.0–20.0	14.5–32.2
Snow removal	12.0–20.0	19.3–32.3
Spreading	6.0–9.0	9.7–14.5

EXAMPLE 5-1

Fifteen miles (24.1 km) of gravel road require reshaping and leveling. You estimate that six passes of a motor grader will be required. Based on operator skill, machine characteristics, and job conditions, you estimate two passes at 4 mi/h (6.4 km/h), two passes at 5 mi/h (8.0 km/h), and two passes at 6 mi/h (9.7 km/h). If job efficiency is 0.80, how many grader hours will be required for this job?

Solution

$$\begin{aligned} \text{Time (h)} &= \left(\frac{2 \times 15}{4.0} + \frac{2 \times 15}{5.0} + \frac{2 \times 15}{6.0} \right) \times \frac{1}{0.80} = 23.1 \text{ h} \quad (\text{Eq 5-2}) \\ &= \left[\left(\frac{2 \times 24.1}{6.4} + \frac{2 \times 24.1}{8.9} + \frac{2 \times 24.1}{9.7} \right) \times \frac{1}{0.80} = 23.1 \text{ h} \right] \end{aligned}$$

Job Management

- to maximize grader production efficiency, it is required:
 - Careful job planning,
 - the use of skilled operators, and
 - competent supervision.
- Use the minimum possible number of grader passes to accomplish the work.
- Eliminate as many turns as possible.