

GE211 Programming in C++ Lab (6)

Objectives of this lab:

- Infinite series implementation.
- Random number implementation.
- Time function

Exercise 1: Estimation of π using Leibniz series

Write a program to calculate the value of (pi '\(\pi\)') using Leibniz series.

$$\frac{\pi}{4} = \sum_{k=0}^{\infty} \frac{(-1)^k}{2k+1}.$$

```
// C++ Lab 6 Exercise 1 Estimation of pi using Leibniz series
//
// Program by: Place your name here

#include <iostream>
#include <cmath>
#define PI 3.14159265359

using namespace std;
int main()
{
    double p = 0.0;
    double x,error;
    int N;

    cout << "Enter the number of N? ";
    cin >> N;
    cout << endl;
    p = 0.0 ;
    for(int k= 1 ; k<=N ; ++k)
    {
        x = -pow(-1,k) / (2*k-1);
        p += x ;
    }
    p = 4*p;
    error = fabs(PI - p) ;
    cout << "N = "<< N << " pi is "<< p << " the error is "<< error << "\n the
percent error is %"<< 100*(error/PI) << endl;

    return 0;
}
```

Enter the number of N? 10

N = 10 pi is 3.23232 the error is 0.0907232
the percent error is %2.88781

Exercise 2: Guessing Game

Write a program that implements a guessing game. The program will generate a random number between 1 and 100 inclusive.

```
/* C++ Lab 6 Exercise 2  guessing game
   Program by: Place your name here
*/

#include<iostream>
#include<cstdlib>
#include<ctime>

using namespace std;

int main()
{
    srand(time(0));
    int number=rand()%100+1;
    int guess, tries(1);

    cout<<"Im thinking of a number between 1-100. Take a guess: ";
    cin>>guess;

    while(guess!=number)
    {
        tries++;

        if(guess>number)
            cout<<"Too high,Guess again: ";
        else
            cout<<"Too low, Guess again: ";

        cin>>guess;
    }
    cout<<"Congrats!! You got it after " << tries << " tries." << endl;

    return 0;
}
```

```
Im thinking of a number between 1-100. Take a guess: 50
Too low, Guess again: 80
Too low, Guess again: 90
Too high,Guess again: 85
Too low, Guess again: 88
Congrats!! You got it after 5 tries.
```

Post Lab

Q1. Modify Ex. 1 so that it finds N that gives any given error limit.

Q2. Use the time function from Ex2 to generate 5 beeps every 10 seconds for 3 times.